

ELECTROFUSION WELDING MACHINE

Electrofusion welders are universal devices used for joining pipes and fittings of thermoplastics (PE, PP, PVDF PB) by resistance method using electrofusion fittings. They are used in the construction and repair of gas pipelines, water pipelines, sewage systems, industrial installations. Thanks to the automatic welding process, the execution of welding is easy, and the resulting connection is characterized by high quality and reliability. The device is very popular among installers making connections of objects to gas and water supply networks.

ZEEN-800 PLUS

Welding machine with welding parameters recording system

TECHNICAL PARAMETERS

Approximate diameter range	~Ø160mm
Power supply	AC 230 [V](+10/-15%), 50[Hz](+10%)
Max power	~3000 W
Weight	13 kg
Dimensions	390 x 240 x 160 mm
Welding voltage	8÷44V
Max starting current	70 A
Max welding current (60%)	30 A
Working temperature	-5÷+40 °C
Interchangeable welding adaptors	Ø4, Ø4.7 mm
Protection class	IP 54
Barcode scanner	Optional (wired or wireless)
Memory	3000 welds
GPS registration (Aerial)	Optional (wired or wireless)
Possibility of printout of welding protocol	✓
Suggested power generator	3,5 kW
Built-in battery	✗
Transmission of welding data onto USB stick	✓
Communication with PC	USB cable
Calibration reminder	✓
Automatic compensation of welding time	✓
Traceability	✓
LCD display (2x16)	✓
User languages	PL, EN, RU, HU, RO, IT, LT, ESP, NO, CZ, SK, DE, FR, NE, LV, UA
Possibility of manual programming	✓
Available data transmission ports	USB type A, USB type B, M12
Possibility of software update by user	✓
Output/power supply cables	3 m/3 m
Power plug	16A 2P
Active fan cooling system	✗



ABOUT

The device supports fittings used in the plumbing and gas industry. It allows four programming modes: manual, scanner, barcode manual, as last. Permanently mounted in a metal transport box, which protects against mechanical damage, sand, rain, and also guarantees convenient transportation of the device. Simple and clear operation of the welding machine control programme. Possibility to connect a barcode scanner (equipment option). Transformer temperature measurement system, protects the welder from overheating.

OPTIONAL EQUIPMENT

- Hand scraper
- Barcode scanner
- Cleaning wipes for welded joints
- Pipe crimper ZRRN-90 (Ø32÷90mm)
- Mounting clamps with joint (PUZN-90L)
- Pipe scissors (Ø16÷63mm)
- Pipe cutter (Ø6÷76mm)
- Pipe cutter (Ø50÷140mm)
- Pipe cutter (Ø110÷160mm)
- Pipe beveler (Ø16÷110mm)
- Pipe beveler (Ø32÷250mm)
- Mechanical pipe scraper ZWUN (Ø32÷160mm)
- Hydraulic crimper ZHRN-160 (Ø90÷160mm) SDR11 and SDR17
- Quick assembly shelter tent 3x3 [m]
- Power generator FOGO FH3001R with voltage stabilisation system (3 kW)

